

ARIZONA LOOSE RANDOM WALL CLADDING



Sandstone is a clastic sedimentary rock composed mainly of sand-sized and silicate grains. Comprising mostly of quartz sand, it can also contain amounts of feldspar and sometimes silt and clay.

White mix sandstone loose random wall cladding is characterised by it's neutral beige colour with warm desert hues that weave throughout.

This cladding is an artisan crafted stone with tumbled and rocky edges to achieve an organic and textural aesthetic.

NOTE: Shade/batch variation is an inherent characteristic of all natural products. The colour of the material supplied may vary to samples/images provided.











Material sandstone

Finish split face

Edge tumbled

APPLICATIONS

Variation

UoM m2

Wall Cladding:	Interior Walls	Yes	
Random sizes up to 400mm Nominal thickness 20-40mm	Exterior Walls	Yes	
	Interior Floors	-	
Corners:			
L shaped corner pieces	Exterior Floors	-	
Random sizes			
Nominal thickness 20-40mm	Splash Areas i.e. shower walls and splashbacks	Yes	
	Wet Areas i.e. shower floors, baths and pools	-	

INSTALLATION + CARE



FORMATS

Sealing may be required. We recommend Chemforce Stain Protector™.

For routine cleaning of internal natural stone surfaces we recommend Chemforce $5+5^{\text{TM}}$ Enzyme Cleaner Concentrate.

Countertop

For routine cleaning of external natural stone surfaces we recommend Chemforce Oxytec-M™ Oxygen Cleaner.

NOTE: Detailed technical data, installation and cleaning guides are available upon request.